



PANOLIN
Bläsimühle 2 – 6
CH-8322 Madetswil
Telefon +41 44 956 65 65
Telefax +41 44 956 65 75
www.panolin.com
info@panolin.com



PANOLIN COMPRESS SYNTH

Compressor oil – fully synthetic

PANOLIN COMPRESS SYNTH:

- Fully synthetic compressor lubricant with additives against oxidation, corrosion, wear and foaming
- Thanks to the synthetic base oils (PAOs and esters), PANOLIN COMPRESS SYNTH is greatly superior to conventional mineral oil based compressor oils: much better viscosity/temperature characteristics; prevents deposits and coking
- Lasts four to six times longer than mineral oil based compressor oils
- Excellent protection against corrosion
- High stability against oxidation
- Good antiredeposition properties
- Inhibits friction and wear
- Economical in use

Applications (follow manufacturer's instructions)

- In reciprocating, screw and turbo-compressors

Note: PANOLIN COMPRESS SYNTH may loosen existing deposits in the system

Performance level

DIN 51 506 VB, VBL, VC, VCL, VDL
ISO 6743/3 A D

Technical data (mean values subject to normal tolerances)

PANOLIN COMPRESS SYNTH	Prod.No.	Density (g/cm ³) at 15 °C	Viscosity (mm ² /s) 40 °C 100 °C	Flashpoint C.O.C., °C	Pour point °C	Viscosity index
46	43140	0.880	46.5 8.3	230	– 45	155
68	43145	0.890	67.5 10.7	244	– 42	148
100	43150	0.892	99.9 15.3	258	– 38	162

Safety-relevant notes:

Please refer to the drum label, or for detailed information, to the safety data sheet (available from PANOLIN)